

(19)

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

EP 0 918 038 A1

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
26.05.1999 Bulletin 1999/21

(51) Int. Cl.<sup>6</sup>: B67B 7/44, B67B 7/16

(21) Application number: 98121932.2

(22) Date of filing: 19.11.1998

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: Farelli, Cesare  
10155 Turin (IT)

(74) Representative:  
Richter, Werdermann & Gerbaulet  
Neuer Wall 10  
20354 Hamburg (DE)


(30) Priority: 21.11.1997 IT TO971019

(71) Applicant: Farelli, Cesare  
10155 Turin (IT)

### (54) Multipurpose tool for opening containers like bottles and cans

(57) Multipurpose implement for opening containers for foodstuffs and other products, stamped in a single piece of adequate thickness, preferably made of stainless steel plate, comprising one end or handle having the shape of a ring (2) with a tab (3), a central part with an oval-shaped hole (7), the edge of which presents two

portions (8, 9) having toothed profiles, with a tab bent back (10) above the hole, the other end being provided with a lug (4), a hook (5) and a toothed curved outer profile (6).



EP 0 918 038 A1

## Description

[0001] It is well known that the consumer frequently encounters difficulties when opening containers for foodstuffs or other products, in particular metal tins or cans and bottles made of glass or thermoplastic material.

[0002] Such operations frequently result in the contents getting spilled in an uncontrolled way, or else may be the cause of accidents involving the user.

[0003] Likewise known is the use of appropriately designed implements for the above-mentioned operations, which, however, present the following drawbacks:

- they do not guarantee maximum efficiency from the functional point of view;
- their use is normally aimed at the opening of a single type of container;
- they are complex and laborious to manufacture, with consequent high production costs;
- frequently they are cumbersome.

[0004] The main purpose of the invention is to eliminate the drawbacks mentioned above.

[0005] The present invention, as it is characterized by the claims, solves the problem of producing a multipurpose implement for opening containers for foodstuffs or other products which achieves the following results:

- multipurpose use for opening metal tins or cans, screw tops and/or metal crown caps for bottles made of glass or thermoplastic material;
- considerable efficiency from the functional point of view;
- maximum safety from the standpoint of accident prevention;
- ease of manufacture, with consequent contained economic cost;
- small overall dimensions, above all if compared to its multipurpose characteristics.

[0006] Additional and more extensive characteristics of the invention are described in what follows, with reference to the attached drawings, in which:

- Figure 1 is a perspective view of the implement stamped in a single piece;
- Figure 2 represents a perspective view of the use of the implement in opening a metal crown cap on a hermetically closed bottle;
- Figure 3 illustrates a perspective view of the use of the implement for partial lifting of the tab for tearing off the lid of a metal tin and/or can;
- Figure 4 is again a perspective view of the use of the implement in the subsequent phase of opening the lid of the metal tin and/or can;
- Figure 5 is a perspective view of how the implement is set for opening the screw top of a bottle made of

glass or thermoplastic material;

Figure 6 presents a perspective view of the use of the implement in the subsequent phase of opening of the screw top of a bottle made of glass or thermoplastic material.

[0007] With reference to Fig. 1, and in accordance with the invention, the multipurpose implement 1, stamped in a single piece and preferably made of stainless steel plate using a special press, comprises one end shaped like a ring 2 with a tab 3 used for opening the pressure caps on bottles, with the additional function of handle for favouring the carrying out of the other functions described in what follows.

[0008] The opposite end consists of a lug 4, a hook 5, and presents a toothed curved outer profile 6, all of which for opening lids of metal tins and/or cans.

[0009] In the central area is made an oval hole 7 with the two opposite ends having different radiuses of curvature and two toothed portions 8 and 9, both with the teeth facing in the left-hand direction of rotation of the implement, on the top of which is located a tab 10, all these parts being used for the opening of screw tops of bottles made of glass or thermoplastic material.

[0010] Basically, the use of the multipurpose implement is as follows:

#### 1. Opening of metal crown caps of hermetically closed bottles (Fig. 2)

- Position the implement 1 so as to engage at the same time the bottom edge of the crown 11 of the cap 12 with the tab 3 of the implement, and the top of the cap with the ring-shaped part 3 of the implement.
- Rotate the implement upwards until the cap 12 is removed from the bottle 13.

#### 2. Tearing off lids of metal tins and/or cans (Figs. 3 and 4)

- With the lug 4, partially lift the tab 14 of the tin or can 15.
- Position the implement so as to insert its hook 5 in the said tab 14.
- Rotate the implement vertically (downwards); as a result of its curved outer profile, the implement engages the raised edge 16 of the tin or can 15 with its teeth, until the lid 17 is completely torn open.

#### 3. Opening of screw tops of bottles made of glass or thermoplastic material (Figs. 5 and 6)

- Engage the larger end of the oval hole 7 of the implement 1 on the screw top 18 of the bottle 19 so that the upper tab 10 rests against the screw top 18. The said bent-back tab 10 has

the purpose both of facilitating the entire operation of opening of the bottle and that of constraining the grip of the teeth 8 and 9 in a central position, i.e., at about one half of the height of the screw top 18.

- Slide the implement 1 forwards so that the two toothed portions 8 and 9 engage the screw top 18, and at the same time rotate the implement itself in the left-hand direction until complete opening of the top is achieved.

6. Multipurpose implement according to Claims 1) and 5), characterized in that the outer part has a toothed curved profile (6) in order to engage the raised edge (16) of the tin or can (15) during opening of the lid (17).

[0011] The features of the implement described above may be summarized as follows:

- multipurpose use for opening metal tins or cans, screw tops and or metal crown caps of bottles made of glass or thermoplastic material or metal;
- considerable efficiency from the functional standpoint;
- maximum safety from the accident-prevention standpoint;
- ease of manufacture, with consequent contained economic cost;
- small overall dimensions, above all if compared with its multiple features of use.

#### Claims

1. Multipurpose implement (1) for opening containers for foodstuffs and other products, stamped in a single piece of adequate thickness, preferably made of stainless steel plate, comprising one end or handle having the shape of a ring (2) with a tab (3), a central part with an oval-shaped hole (7), the edge of which presents two toothed portions (8, 9), with a tab bent back (10) above the hole, the other end consisting of a lug (4), a hook (5) and a toothed curved outer profile (6).
2. Multipurpose implement according to Claim 1), characterized in that the oval-shaped hole (7) presents the two opposite ends with two different radiuses of curvature.
3. Multipurpose implement according to Claims 1) and 2), characterized in that the two portions (8, 9) are both with the teeth facing in the left-hand direction of rotation of the implement itself.
4. Multipurpose implement according to Claims 1), 2) and 3), characterized in that the distance of the tab bent back (10) with respect to the implement corresponds to about one half the height of the screw top (18).
5. Multipurpose implement according to Claim 1), characterized in that the part (5) is shaped like a hook.

BEST AVAILABLE COPY

FIG. 1








FIG. 2





BEST AVAILABLE COPY





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 98 12 1932

BEST AVAILABLE COPY

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	DE 36 31 705 A (MERSINGER HEINZ) 24 March 1988 * column 1, line 47 - line 51; figure 1 *	1	B67B7/44 B67B7/16
A	US 1 990 289 A (KRUEGER, HERMAN S.) 5 February 1935		
A	DE 25 56 294 A (ROHRWASSER HANS W) 16 June 1977		
A	EP 0 138 184 A (BERENDSOHN AG) 24 April 1985		
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B67B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 25 February 1999	Examiner Müller, C
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (Pdc01)

ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 98 12 1932

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-02-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 3631705	A	24-03-1988	NONE	
US 1990289	A	05-02-1935	NONE	
DE 2556294	A	16-06-1977	NONE	
EP 0138184	A	24-04-1985	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82